



DIN-rail cabinet with 2 rows

# Datasheet

## DIN-rail cabinets (703-001-90xx)

Prima DIN-rail cabinets	
<b>703-001-9012 (1 row)</b>	
Specifications	1 row of 12DIN modules (1 x 12M)
Size (L x H x D)	287mm x 263mm x 112mm
<b>703-001-9024 (2 rows)</b>	
Specifications	2 rows of 12DIN modules (2 x 12M)
Size (L x H x D)	287mm x 361mm x 112mm
<b>703-001-9036 (3 rows)</b>	
Specifications	3 rows of 12DIN modules (3 x 12M)
Size (L x H x D)	287mm x 482mm x 112mm
<b>Housing</b>	
Material	Self-extinguishing technoplastic, resistant to fire and abnormal heat 650°C/30 min, white RAL9003
IP protection	IP40
Supplements	Battery (800-000-5002), Battery cable (703-000-0002), Battery shelf (Battery shelf), Lock (703-000-9009), Tamper magnet switch (800-000-9001)
Compliance with standards	IEC 60670-1-24



DIN-rail cabinet with 2 rows

Prima DIN-rail cabinets	
<b>703-001-9001 (1 row)</b>	
Specifications	1 row of 12DIN modules (1 x 12M)
Size (L x H x D)	256mm x 200mm x 94mm
<b>703-001-9002 (2 rows)</b>	
Specifications	2 rows of 12DIN modules (2 x 12M)
Size (L x H x D)	256mm x 326mm x 96mm
<b>703-001-9003 (3 rows)</b>	
Specifications	3 rows of 12DIN modules (3 x 12M)
Size (L x H x D)	256mm x 451mm x 96mm
<b>Housing</b>	
Material	Self-extinguishing technoplastic, resistant to fire and abnormal heat 650°C/30 min, white RAL9003
IP protection	IP40
Supplements	Battery (800-000-5002), Battery cable (703-000-0002), Tamper magnet switch (800-000-9001)
Compliance with standards	IEC 60670-1-24