



Datasheet

Vandal-proof 21.5" booking screen incl. power cable, antenna, mounting rail and key



The booking terminal offers both horizontal and vertical mounting and display functionality

Technical data	
Power supply	100 ~ 240ACV 50/60Hz
Maximum power consumption	30W
Standby power consumption	<1W
Operating temperature	0°C to 50°C
Storage temperature	-20°C to +60°C
Working humidity	10% ~ 85%
Storage humidity	5% ~ 95%
Lifetime	60,000hrs
Input and Output	
VGA output	1
HDMI output	1
LAN	1
WIFI	1
USB	2
Speaker	2x5W(9Ω)
Touch panel	
Specification	Capacitive touch
Positioning accuracy*	±2mms
Transmittance	≥92%
Hardness	7H
Click manner	10 points
Response time	≤4ms
Output Resolution	4096*4096
Life time	more than 600 million times
OS system	
Android O/S	Android 4.2.2
CPU	Cortex A9, Quad core 1.5G
Main GPU frequency	MALI 400 MP2
Memory	1G
Storage	4G

Screen	
Panel size	21.5" LCD panel, LED backlight
Display area	475.2mm*267.3mm (16:9)
Color system	PAL/NTSC/SECAM
Maximum resolution	1920*1080
Display color	16.7M
Pixel pitch	0.2475mm
Brightness (Tamper switch)	300d/m ²
Contrast	1000*1
Visual angle	178°/178°
Response time	5ms
Screen menu display	
Menu language	Chinese/English
Housing	
Size	W: 50mm x L: 540mm x H: 330mm
Installation	Wall-mounted
Casing	Metal case SPCC
Tempered glass	Yes
Color	Black
Quality standard	ISO9001, CCC
Weight	5500g